

ELECTRIC LIFTING PLATFORM

Multiple uses such as: lifting and lowering materials, level compensation when fitting machines, installations in conveyor system etc.

Compact hydraulic design with all safety components complying to EN1570,

High pressure cylinder with dual safety function.

Hard chrome plated piston rods.

Lift and lower by easily push buttons to reach the ergonomically correct working height.

With emergency switch off and a 3m long control cable.

With different loading capacity up to 3000kg for your option.



LOW PROFILE ELECTRIC LIFTING PLATFORM

Compact hydraulic design with all safety components complying to En1570, High pressure cylinder with dual safety function.

- Hard chrome plated piston rods.
- Lift and lower by easily push buttons to reach the ergonomically correct working height.
- With emergency switch off and a 3m long control cable.
- With different loading capacity up to 3000kg for your option.
- The tried and trusted lift table with sturdy construction.
- Multiple uses such as: lifting and lowering materials, level compensation when fitting machines, installations in conveyor system etc.



Electric Lifting Platform										
1KG=2.2LB 1INCH=25.4MM										
Model	ELF10A -24X48	ELF10A -48X48	ELF15A -36X48	ELF20A -48X48	ELF25A -32X56	ELF25A -48X72	HIW1.0EU	HIW2.0EU	HIW4.0EU	HIW3.0EU
Capacity (kg)	1000	1000	1500	2000	2500	2500	500	1000	2000	3000
Lowered height (mm)	200	200	200	200	250	250	190	190	190	220
Raised height (mm)	990	990	990	990	1200	1200	1010	1010	1010	1020
Platform size (LxW)(mm)	1220X610	1220X1220	1220X915	1220X1220	1420X815	1830X1220	1300X800	1300X800	1300X800	1300X800
Net weight (kg)	250	340	320	380	400	700	160	220	280	320
Lifting time with load (s)	20	20	25	50	60	60	15	25	40	26
Lifting speed with load (mm/s)	39	39	31	16	16	16	55	40	22	30
Lowering speed with load (mm/s)	64	64	64	35	20	20	40	35	33	40
Motor (kw)	0.75	0.75	0.75	0.75	1.5	1.5	0.75	0.75	0.75	1.5
Optional Voltage	115V, 60HZ, single-phase / 230V, 50HZ, single-phase / 380V, 50HZ, 3-phase						230V, 50HZ, single-phase / 380V, 50HZ, 3-phase			380V, 50HZ, 3-phase

Low Profile Electric Lifting Platform			
1KG=2.2LB 1INCH=25.4MM			
Model	HTFG05	HTF-G10	HTF-G20
Capacity (kg)	500	1000	2000
Lowered height (mm)	85	82	100
Raised height (mm)	760	760	1000
Platform size (LxW)(mm)	1020X610	1450X1140	1560X1140
Net weight (kg)	96	250	376
Lifting time with load (s)	10	18	55
Lifting speed with load (mm/s)	75	42	16
Lowering speed with load (mm/s)	34	48	23
Motor (kw)	0.75	0.75	0.75
Optional Voltage	115V, 60HZ, single-phase / 230V, 50HZ, single-phase / 380V, 50HZ, 3-phase	230V, 50HZ, single-phase / 380V, 50HZ, 3-phase	230V, 60HZ, 3-phase / 230V, 50HZ, single-phase / 380V, 50HZ, 3-phase

U-shape	
1KG=2.2LB 1INCH=25.4MM	
Model	HTF-U10
Capacity (kg)	1000
Lowered height (mm)	80
Raised height (mm)	760
Platform size (LxW)(mm)	1450X1140
Net weight (kg)	235
Lifting time with load (s)	18
Lifting speed with load (mm/s)	42
Lowering speed with load (mm/s)	48
Motor (kw)	0.75
Optional Voltage	230V, 50HZ, single-phase / 380V, 50HZ, 3-phase

U-SHAPE ELECTRIC LIFTING PLATFORM

This 'U' shaped lift platform is ideal for lifting pallets or cages to a safe working height and suited for use as a feeding table on an assembly line.

- Supplied with remote power system and control unit with UP, DOWN and EMERGENCY STOP controls.
- The 'U' shape allows a pallet truck to position the pallet / cage onto the lift platform.
- Overload by-pass valve protects operator and pump.

