

## Mobile Stainless Scissor Lift Tables

Capacity: 100kg-450kg

Optional various table sizes & lift heights

Stainless steel for anti-corrosion applications (Attention: Scissors & Pumps are galvanized)

| Model  | Capacity (kg) | Material        | Length of table(mm) | Width of table(mm) | Min.height (mm) | Max.height (mm) |
|--------|---------------|-----------------|---------------------|--------------------|-----------------|-----------------|
| TFD15S | 100           | stainless steel | 700                 | 445                | 250             | 1220            |
| TF30S  | 250           | stainless steel | 815                 | 500                | 290             | 890             |
| TFD35S | 350           | stainless steel | 910                 | 500                | 355             | 1295            |
| TF50S  | 450           | stainless steel | 815                 | 500                | 290             | 890             |



## ELECTRIC TABLE LIFTER

### Electric Table Truck

1KG=2.2LB 1INCH=25.4MM

| TYPE  |      | ETF30      | ETF50       | ETF75       | ETFD35     |
|---|------|------------|-------------|-------------|------------|
| Capacity Q                                      | Kg   | 300        | 500         | 750         | 350        |
| Max.Table Height h <sub>t</sub>                 | mm   | 880        | 1025        | 970         | 1300       |
| Min.Table Height h <sub>1</sub>                 | mm   | 290        | 440         | 420         | 370        |
| The Dimension Of Table Size (L*B)               | mm   | 850x500x50 | 1010x520x50 | 1000x510x55 | 910x500x53 |
| Caster Wheel d                                  | mm   | φ125x40    | φ150x48     | φ147x50     | φ125x40    |
| Overall Length L                                | mm   | 1145       | 1305        | 1345        | 1210       |
| Height Of Handle From The Ground h <sub>2</sub> | mm   | 920        | 970         | 935         | 920        |
| Lifting speed with load/without load            | mm/s | 65/94      | 65/94       | 70/80       | 90/110     |
| Lowering speed with load/without load           | mm/s | 98/74      | 98/74       | 50/35       | 100/90     |
| Lifting Cycle (fully charged)                   |      | 120        | 100         | 100         | 100        |
| Battery   |      | 2x12/15    | 2x12/24     | 2x12/15     | 2x12/15    |
| Vertical Travel h <sub>3</sub>                  | mm   | 590        | 585         | 550         | 930        |
| Lifting Motor (DC24V KW)                        |      | 0.8        | 0.8         | 0.8         | 0.8        |
| Charger (built-in)24V3A                         |      | 8.5Hr      | 8.5Hr       | 8.5Hr       | 8.5Hr      |
| Approx Lifting Speed                            |      | 10         | 10          | 12          | 10         |
| Net Weight                                      | Kg   | 115        | 157         | 160         | 142        |



**350kg capacity  
1.3m Height  
Table:910x500mm  
Double scissor lift**

Ideally suited for use as a feeding table on an assembly line.

Excellent hydraulic unit for raising table top to desired height.

Electrically operated table descent control.

Industrial Equipment