




ECONOMICAL MANUAL STACKER

Ideal and economic choice for manual transport and lifting, with its different mast options (1600, 3000 mm) and diverse lifting capacity (500kg, 1000kg) enables to deal with a large number of applications in the warehouse or any other facilities. For example, with the lift capacity of 1000 kg and lifting height of 1600mm, therefore the truck is an ideal and economic choice suitable for first level stacking.

- The minimized turning radius and compact size of the truck allows it to be used in the most confined space and narrow aisle such as in stores, small warehouses and factories.




Easy and comfortable handling through ergonomically handles, effortless pulling during transport with long tiller



We can offer additional protection for the operator through foot protection on the steering rollers. Safe parking in any situation with mechanical parking brake.

Model EFS Series		1KG-2.2LB 11INCH-25.4MM				
ITEM/TYPE		EFS0516G	EFS1016	EFS1016G	EFS1030	EFS1030B
Capacity Q	Kg	500	1000	1000	1000	1000
Load center c	mm	600	500	600	600	500
Max.Fork Height	mm	1600	1600	1600	3000	3000
Lowered Fork Height	mm	85	80	85	85	80
Fork Adjust Width	mm	550	300-800	550	550	300-740
Fork Width	mm	150	140	160	160	140
Fork Length	mm	1050	900	1150	1150	900
Overall length	mm	1520	1488	1660	1668	1496
Overall height	mm	2010	1980	2010	2060	2060
Overall width	mm	820	850	740	740	800
Ground Clearance	mm	28	20	25	25	23
Front Wheel	mm	φ 74x55	φ 74x55	φ 74x55	φ 74x70	φ 74x70
Rear Wheel	mm	φ 150x42	φ 180x50	φ 180x50	φ 180x50	φ 180x50
Net weight	Kg	156	184	172	310	332



Optional choice of fixed fork (550*1150mm) and adjustable fork (330-800*900mm)

Conforms to EN1757-1





Manual & Semi-Electric Stacker

STANDARD MANUAL STACKER

Ideal and economic choice for manual transport and lifting, with its different mast options (1600, 2500, 3000 mm) and diverse lifting capacity (500kg, 1000kg, 1500kg) enables to deal with a large number of applications in the warehouse or any other facilities. For example, with the lift capacity of 1000 kg and lifting height of 1600 mm, therefore the truck is an ideal and economic choice suitable for first level stacking.

Hand Stacker		1KG=2.2LB 1INCH=25.4MM		
ITEM/TYPE		SFH10	SFH15	SFHD10
Capacity Q	Kg	1000	1500	1000
Min. fork height h ₁	mm	85	85	85
Max. fork height h ₂	mm	1600	1600	2500
Min. mast height h ₃	mm	1980	1980	1830
Size of fork e's	mm	150/160x60	150/160x60	150/160x60
Length of fork L	mm	900/1150	300/1150	900/1150
Width of overall fork (adjust/fix) b5	mm	330-740/550	330-740/550	330-740/550
Radius of gyration	mm	1250/1380	1250/1380	1250/1380
Weight	Kg	220	260	300
Fork rollers	mm	φ74x70	φ74x70	φ74x70
Big wheel	mm	φ180x50	φ180x50	φ180x50

Conforms to EN1757-1



- Easy and comfortable handling through ergonomically handles, effortless pulling during transport with long tiller.
- Optional choice of fixed fork (550X1150mm) and adjustable fork (330-740X900mm).
- We can offer additional protection for the operator through foot protection on the steering rollers.
- Safe parking in any situation with mechanical parking brake.
- Optional tiller pumping lifting and foot pedal lifting

